



ROOFING
SYSTEMS

fatra

Fatra FA1 Butyl Sealing Tape

Product Description

Strip Sealant for sealing VCL's



FA1 Butyl Strip sealant is generally used to seal the joints of Fatra Polythene Vapour Control Layers. It is manufactured from a high-tack formula which provides the necessary seal for these applications.

Strip Sealant for air-sealing deck laps



Where air-tightness of the steel deck is critical, the best way of achieving sufficient results is to use strip sealants on the laps. The range of strip sealants that we offer have been selected to suit the current specifications and provide options to suit all applications found on a flat roof.



ROOFING MEMBRANES



ROOFING
SYSTEMS

fatra

ROOFING MEMBRANES

Strip Sealant Features

- Consistent seal simply achieved
- High-grade butyl rubber compound
- Supplied on a roll, for ease of application
- High performance
- Extra-flexible and extra-strong
- High tack
- Standard colour - grey
- Black and white available to special order

Physical Characteristics

Fatrafol FA1 Butyl Sealing Tape			
Thickness x Width (mm)	Roll length (m)	Rolls per carton	Product Code
1 x 12	45	20	FA1

Other sizes available

Technical Data

Fatrafol FA1 Butyl Sealing Tape	
	Class A
Density	1.6
Elongation at break (%)	220
Force to compress by 20% (N)	220
Joint movement accommodation	± 15
Temperature (°C)	-40~110
Service life (years)	20
Sheer strength (N)	16.2
Tack	Very good
UV resistance	Very good